


Yoke Grade 8 Excavator Weld-on Hook BS EN 1677-1

- Manufactured from forged alloy steel, quenched and tempered.
- Manufactured and tested in accordance with EN1677-1.
- Certified by DGVV GS-OA-15-03.
- Load rated parts are 100% magnaflux crack detected.
- Individual forged parts are traceable to Test Certification.
- Proof tested to 2.5 times the WLL.
- Fatigue rated to 1.5 times the WLL.
- Design Factor 5 : 1

USES

- Designed to be a permanent slinging attachment point for jibs and arms on mobile excavators



METRIC SPECIFICATIONS

Part Code	WLL tonnes	F mm	H mm	L mm	P mm	T mm	W mm	HV mm	a mm	Box Quantity	Mass Kg
8-081-01	1.0	25	27	70	18	18	95	7	4	24	0.6
8-081-02	2.0	30	30	85	25	20	115	8	5	18	1.0
8-081-03	3.0	35	30	107	28	23	133	9	6	12	1.4
8-081-04	4.0	42	38	114	28	30	142	10	7	12	2.2
8-081-05	5.0	44	47	135	30	31	167	12	7	6	3.0
8-081-08	8.0	50	52	137	32	39	176	12	8	6	3.7
8-081-10	10.0	56	56	170	44	42	222	13	8	4	6.2

IMPERIAL SPECIFICATIONS

Part Code	WLL lbs	F inch	H inch	L inch	P inch	T inch	W inch	HV inch	a inch	Box Quantity	Mass lbs
8-081-01	2,200	0.98	1.06	2.83	0.71	0.67	3.74	0.28	0.24	24	1.3
8-081-02	4,400	1.18	1.22	3.46	0.98	0.79	4.53	0.31	0.31	18	2.2
8-081-03	6,600	1.38	1.18	4.21	1.1	0.91	5.24	0.35	0.39	12	3.1
8-081-04	8,800	1.65	1.5	4.41	1.1	1.18	5.55	0.39	0.43	12	4.4
8-081-05	11,000	1.73	1.81	5.24	1.18	1.22	6.57	0.47	0.51	6	6.6
8-081-08	17,600	1.97	2.13	5.39	1.26	1.54	6.89	0.47	0.55	6	8.4
8-081-10	22,000	2.2	2.2	6.61	1.73	1.65	8.74	0.51	0.63	4	13.9

We recommend that the working load limit should be reduced to meet any appropriate legislative requirements, if welding on to an excavator.